ENOVATIVE® MANUFACTURING LLC

AutoHot®

JOB or CUSTOMER:					
ENGINEER:					
CONTRACTOR:					
SUBMITTED BY:		APPROVED BY:		ORDER NO:	
Date:		Date:		Date:	

SUBMITTAL | SPECIFICATIONS

RM-ROU-001

for use with AutoHot EMS Remote Monitoring Feature
(KuWFi Wi-Fi Router | 300Mbps | Waterproof | Router | 4G Sim Card)



Description

Cellular router for providing remote monitoring access of any AutoHot commercial EMS. Outdoor 4G LTE router with POE adapter for easy installation of wireless connectivity for remote office locations. Wired Ethernet and 3G/4G wireless WAN connections are available.

We will set up the router if it is purchased at the same time as the commercial AutoHot controller. If this item is purchased separately, the router will be ready for plug and play but the commercial AutoHot controller will need to be configured to connect to the router, similar steps as connecting a smart phone to the Wi-Fi Network.

- Can be used for indoor and outdoor use.
- The router is ready for plug and play.
- Internet connection sharing, multiple devices, as long as they are in range, can access the WiFi network at the same time.
- The download speed is up to 150 mbps, upload speed is up to 50 mbps, and wireless transmission speed is 300 mbps.
- Reduces co-channel interference, expands the wireless transmission range, and eliminates dead zones.
- The waterproof and dust proof casing ensures it can withstand harsh outdoor climates and indoor industrial environments.
- If credentials are changed, the commercial AutoHot controller will need to be configured to connect to the router.

Monthly Subscription

There is a monthly subscription for this service. Please call us for more details.

1 x Outdoor 4G LTE CPE Router	1 x Stand Holder	1 x User Manual	1 x POE Power Supply	1 x RJ45 Cable

SPECIFICATIONS

Power	120 VAC
Range	200 ft diameter
IP65 grade shell design	Waterproof, Dustproof, Lightning protection, High and low temperature resistance
Built-in 5dBi antenna	Download speed up to 150mbps, Upload speed up to 50mbps, Wireless speed up to 300mbps.
Operating Temperature	Normal: 0°C to +45°C;
Operating Humidity	-20°C to +70°C 5%~ 95%
Weight	13.4 ounces
Dimensions	6.7 × 3.5 × 1.6 in
Color	White
Mounting	Two holes on back for mounting